





## Stand-Alone IIoTA™

DIN Mount IIoTA MiNi™

Part Number	IIOTA-1.0 <i>-xxx</i> <sup>1</sup>	IIOTA-MiNi-xxx <sup>1</sup>
Network Interface #1	1000/100/10baseT	
Network Interface #2	100/10baseT	
Network Security	Integrated Hardened Gateway	
Device Connections	0 to 100 (increments of 5) 1	0 to 20 (increments of 5) <sup>1</sup>
Drag & Drop Dashboard Tool	Yes	To Be Released
Pre-Installed Database Server	DB2	MySQL
Integrated Web Server	Yes	
Compatible App's	Workflow Manager <sup>2</sup>	N/A
Power	+5V @ 1.2A, 115/240 VAC	24 Vdc @ 0.25A
Case	IP Rated Cast Aluminum Enclosure	DIN-Style Enclosure
Dimensions WxHxD in/(mm)	7.08" x 7.28" x 3" (180 x 185 x 76)	2.125" x 5.98" x 4.09" (54 x 152 x 104)
Cooling	Passive	
Temperature	-60°C to 80°C	0°C to +70°C
Hardware Warranty	12 months Limited Warranty	
Certifications	UL, CE	
Included in Package	AC Power Plug, Quick Start Guide	Quick Start Guide
The number of device connections to be and added as a three digit suffix (-xxx) of a licensing Required	e specifed in increments of 5 connections at the time of order (e.g. IIOTA-1.0-015)	

<sup>2</sup> Licensing Required